

 **419-480-9118**
 **cs@toledo-tools.com**
 **www.toledo-tools.com**

TOLEDO TOOLS

PRODUCT CATALOG

Toledo Tools

Toledo, Ohio 43614
United States
419-480-9118 
cs@toledo-tools.com 

**SUPER DOPE ANAEROBIC PIPE THREAD SEALANT - 350ML (12OZ) BRUSH TOP FITS
LOCTITE® 565 - QTY 120**

SKU: SD-350MLBR-120
PRICE: \$2,839.99



**PRODUCT
DESCRIPTION**

Super Dope Anaerobic Pipe Thread Sealant is designed for the sealing and locking between metal pipe and metal fittings. Super Dope chemically hardens in the absence of air between close fitting metal surfaces. An instant low pressure seal is obtained up to 100 PSI and after curing occurs can withstand up to 10,000 PSI. This make fittings virtually impossible to leak. Super Dope also allows for adjustment and alignment of fittings after installation. If the installation needs to be removed or moved disassembly is permitted. Super Dope can withstand temperatures up to 400° F. This product can be Compared to LOCTITE® 565.

- Brush Top for quick application
- Instant low pressure seal (100 PSI, Max: 10,000)
- Cures to pipe burst pressure
- Allows for adjustment and alignment of fittings after application
- Permits disassembly
- Pipe joints and fittings are locked against vibration loosening
- Withstands temperature up to 400° F
- Cross Reference: LOCTITE® 565
- Bottle Size: 350 ML / 12 OZ
- Case Quantity: 120

ADDITIONAL INFORMATION

More Information	
Manufacturer	Super Dope
Description	Super Dope Anaerobic Pipe Thread Sealant is designed for the sealing and locking between metal pipe and metal fittings. Super Dope chemically hardens in the absence of air between close fitting metal surfaces. An instant low pressure seal is obtained up to 100 PSI and after curing occurs can withstand up to 10,000 PSI. This make fittings virtually impossible to leak. Super Dope also allows for adjustment and alignment of fittings after installation. If the installation needs to be removed or moved disassembly is permitted. Super Dope can withstand temperatures up to 400° F. This product can be Compared to LOCTITE® 565. • Brush Top for quick application • Instant low pressure seal (100 PSI, Max: 10,000) • Cures to pipe burst pressure • Allows for adjustment and alignment of fittings after application • Permits disassembly • Pipe joints and fittings are locked against vibration loosening • Withstands temperature up to 400° F • Cross Reference: LOCTITE® 565 • Bottle Size: 350 ML / 12 OZ • Case Quantity: 120

 **419-480-9118**

 **cs@toledo-tools.com**

 **www.toledo-tools.com**

TOLEDO TOOLS