

 **419-480-9118**
 **cs@toledo-tools.com**
 **www.toledo-tools.com**

TOLEDO TOOLS

PRODUCT CATALOG

Toledo Tools

Toledo, Ohio 43614
United States

419-480-9118 
cs@toledo-tools.com 

TUF-CUT™ CLEAR PIPE THREAD CUTTING OIL - 1 GALLON FOR USE WITH RIDGID® 70835 300 535 1224 700 690 THREADING MACHINES - QTY 30

SKU: TC-CL-01G-30

PRICE: \$739.99



PRODUCT DESCRIPTION

Tuf-Cut™ Clear Pipe Thread Cutting Oil is the next generation in performance drilling, threading and cutting fluids. This product is designed and engineered to offer extended tool life under severe applications working with all types of metals. It separates from chips and fines efficiently and produces an excellent finish on machined parts.

This versatile fluid is manufactured with synthetic and hydro-treated base stocks, along with the latest generation of performance based additive technologies.

Tuf-Cut™ Clear Pipe Thread Cutting Oil has passed all stringent testing requirements to meet the NSF/ANSI Standard 14 for use in contact with CPVC and PVC. This fluid is designated FGG/BM/CZ

- Container Size: 1 Gallon - Quantity 30
- NO Sulphur - NO Fumes! Ideal product if air circulation is a problem.
- Clear Oil - Traditional high performance mineral oil formulated to produce superior quality threads on stainless steel and black pipe.
- Cools threads and pipe during operation
- Light mineral oil base provides better lubrication and heat dispersion characteristics and prevents binding and catching of dies.
- Tuf Cut is recommended for prolonging the life of pipe threading dies and other steel cutting tools including drill bits, holesaws and reciprocating blades.
- Meet the NSF/ANSI Standard 14 for CPVC and PVC pipe.
- Flash point: 320.4° F (160.22° C)
- Working Viscosity: -32.8° F (-36° C)

Also suitable for other applications: Threading, Gear Cutting, Shaving, Deep Drilling, Reaming, Honing, Lapping, Turning, Milling, Broaching, Tapping

ADDITIONAL INFORMATION

More Information

Manufacturer Tuf-Cut

Description

Tuf-Cut™ Clear Pipe Thread Cutting Oil is the next generation in performance drilling, threading and cutting fluids. This product is designed and engineered to offer extended tool life under severe applications working with all types of metals. It separates

from chips and fines efficiently and produces an excellent finish on machined parts.

This versatile fluid is manufactured with synthetic and hydro-treated base stocks, along with the latest generation of performance based additive technologies.

Tuf-Cut™ Clear Pipe Thread Cutting Oil has passed all stringent testing requirements to meet the NSF/ANSI Standard 14 for use in contact with CPVC and PVC. This fluid is designated FGG/BM/CZ

- Container Size: 1 Gallon - Quantity 30
- NO Sulphur - NO Fumes! Ideal product if air circulation is a problem.
- Clear Oil - Traditional high performance mineral oil formulated to produce superior quality threads on stainless steel and black pipe.
- Cools threads and pipe during operation
- Light mineral oil base provides better lubrication and heat dispersion characteristics and prevents binding and catching of dies.
- Tuf Cut is recommended for prolonging the life of pipe threading dies and other steel cutting tools including drill bits, holesaws and reciprocating blades.
- Meet the NSF/ANSI Standard 14 for CPVC and PVC pipe.
- Flash point: 320.4° F (160.22° C)
- Working Viscosity: -32.8° F (-36° C)

Also suitable for other applications: Threading, Gear Cutting, Shaving, Deep Drilling, Reaming, Honing, Lapping, Turning, Milling, Broaching, Tapping



419-480-9118



cs@toledo-tools.com



www.toledo-tools.com

TOLEDO TOOLS